Article Number

2015

2000 010T

1871

8405

102595-02-M-1540

Restricted Delivery? (Extra Fee)

D g

☐ Insured Mall

SENDER: COMPLETE THIS SECTION

COMPLETE THIS SECTION ON DELIVERY

A. Signature

Article Addressed to:

Mr. Dudley M. Pattie General Manager Rapidan Service Authority

P. O. Box 148

Ruckersville, VA 22968

Joan C. Crowther

Service Type
The Certified Mail
Registered

D Express Right
To Return Receipt for Merchandise
C.O.D.

so that we can return the card to you.

Attach this card to the back of the mailpiece,

B. Received by (Printed Name)

C. Date of Delivery

☐ Agent☐ Addressee

D. Is delivery address diffeger

If YES, enter delivery exerces below: 7

Z □ Yes

MAR 22 2013

8967

or on the front if space permits.

Complete items 1, 2, and 3. Also complete item 4 if Restricted Delivery is desired.

Print your name and address on the reverse

國USPS.COM

Search USPS.com or Track Packages



Track & Confirm

GI	T EMAIL UPOATES PRINT DETAILS		<u> </u>	San	And the second s	New York (Section)
	YOUR LABEL NUMBER	SERVICE	STATUS OF YOUR ITEM	DATE & TIME	LOCATION	FEATURES
	70121010000218718405	4.7	Delivered	March 22, 2013, 10:44 am	RUCKERSVILLE, VA 22968	1
	,		Available for Pickup	March 22, 2013, 10:24 am	RUCKERSVILLE, VA 22968	
			Arrival at Unit	March 22, 2013, 9:23 am	RUCKERSVILLE, VA 22968	

Check on Another Item

What's your label (or receipt) number?



Privacy Policy No FEAR Act EEO Data

ON USPS.COM

Government Services > Buy Stamps & Shop >

ON ABOUT USPS.COM

About USPS Home

Copyright@ 2013 USPS, All Rights Reserved

(Domestic Mail On	MAILTM RECI	verage Provided)					
For delivery information visit our website at www.usps.com							
OFF		USE					
Postage	\$	Crowther 3-20-13					
Certified Fee		3-20-19 Postmark					
Return Recelpt Fee (Endarsement Required)		Here					
Restricted Delivery Fee (Endorsement Required)							
Total Postage & Fees	Mr. Dudley M. Pattie						
Sent To	General Manager Rapidan Service Au	thority					
Street, Apt. No.; or PO Box No.	P. O. Box 148 Ruckersville, VA 22						
City, State, ZIP+4	Joan C. Crowther						

Crowther, Joan (DEQ)

From:

Thompson, Alison (DEQ)

Sent:

Friday, March 29, 2013 2:48 PM

To:

Daub, Elleanore (DEQ); Vice, Rebecca (DEQ)

Cc: Subject: Crowther, Joan (DEQ); Thomas, Bryant (DEQ); Young, April (DEQ); Johnson, Rebecca (DEQ)

VA0021105 Gordonsville STP

The VPDES permit for the Gordonsville STP has been reissued with an effective date of March 20, 2013. All pertinent reissuance documents will be uploaded to Filenet within the next 30 days. If you need any information sooner, please contact Joan Crowther.

Alison Thompson
Water Permits Technical Reviewer
Virginia Dept of Environmental Quality
Northern Regional Office
13901 Crown Ct
Woodbridge, VA 22193
(703) 583-3834
alison.thompson@deg.virginia.gov

Crowther, Joan (DEQ)

From:

Thompson, Alison (DEQ)

Sent:

Friday, March 29, 2013 2:50 PM

To:

Ford.Nancy@epamail.epa.gov; Smith.Mark@epamail.epa.gov

Cc:

Thomas, Bryant (DEQ); Crowther, Joan (DEQ)

Subject:

VPDES Permit VA0021105 Gordonsville STP - Minor Municipal

Documentation supporting the reissuance of the VPDES permit for the Gordonsville STP, VPDES Permit #VA0021105, is posted at http://www.deq.virginia.gov/fileshare/wps/EPA/NRO/VA0021105/ The following final documents will be posted within the next 30 days: a

transmittal letter, the final signed permit, permit application, and the fact sheet with all attachments.

Please let us know if you need additional information. If you need a copy of any of the documents sooner, please feel free to contact the permit writer (<u>Joan.Crowther@deq.virginia.gov</u>).

Respectfully,

Alison Thompson (for Bryant Thomas)

Alison Thompson
Water Permits Technical Reviewer
Virginia Dept of Environmental Quality
Northern Regional Office
13901 Crown Ct
Woodbridge, VA 22193
(703) 583-3834
alison.thompson@deq.virginia.gov



COMMONWEALTH of VIRGINIA

DEPARTMENT OF ENVIRONMENTAL QUALITY

Douglas W. Domenech Secretary of Natural Resources NORTHERN REGIONAL OFFICE 13901 Crown Court, Woodbridge, Virginia 22193 (703) 583-3800 Fax (703) 583-3821 www.deq.virginia.gov

David K. Paylor
Director

Thomas A. Faha Regional Director

March 20, 2013

Mr. Dudley M. Pattie General Manager Rapidan Service Authority P. O. Box 148 Ruckersville, VA 22968

CERTIFIED MAIL
RETURN RECEIPT REQUESTED

Re: VPDES Permit No. VA0021105, Town of Gordonsville Wastewater Treatment Plant, Orange County

Dear Mr. Pattie:

The Department of Environmental Quality (DEQ) has approved the enclosed effluent limitations and monitoring requirements for the above-referenced permit. Copies of your permit and fact sheet are enclosed.

A Discharge Monitoring Report (DMR) form is no longer included in the reissuance package. DEQ has launched an electronic DMR (e-DMR) program that allows you to submit the effluent monitoring data electronically, and we expect every permittee to use e-DMR as permits are issued or reissued. The first electronic DMR submittal for May 2013 is due by June 10, 2013. Please reference the effluent limits in your permit and report monitoring results in e-DMR to the same number of significant digits as are included in the permit limits for the parameter. Answers to frequently asked questions about the e-DMR system, including the e-DMR registration process, are available at the following website:

http://www.deq.virginia.gov/Programs/Water/PermittingCompliance/ElectronicDMRsubmissions.aspx. The regional contact for e-DMR is Rebecca Vice; she can be reached at (703) 583-3922 or by e-mail at Rebecca.Vice@deq.virginia.gov.

As provided by Rule 2A:2 of the Supreme Court of Virginia, you have thirty days from the date of service (the date you actually received this decision or the date it was mailed to you, whichever occurred first) within which to appeal this decision by filing a notice of appeal in accordance with the Rules of the Supreme Court of Virginia with the Director, Department of Environmental Quality. In the event that this decision is served on you by mail, three days are added to that period.

Alternately, any owner under §§ 62.1-44.16, 62.1-44.17, and 62.1-44.19 of the State Water Control Law aggrieved by any action of the State Water Control Board taken without a formal hearing, or by inaction of the Board, may demand in writing a formal hearing of such owner's grievance, provided a petition requesting such hearing is filed with the Board. Said petition must meet the requirements set forth in §1.23(b) of the Board's Procedural Rule No. 1. In cases involving actions of the Board, such petition must be filed within thirty days after notice of such action is mailed to such owner by certified mail.

A Reliability Class II is assigned to this facility and this facility has Class II licensed operator requirements.

Mr. Dudley M. Pattie VA0021105 Reissuance Final Permit to Facility Page 2 of 2

If you have questions about the permit, please contact Joan C. Crowther at (703)583-3925, or by joan.crowther@deq.virginia.gov.

Respectfully,

Bryant Thomas

Water Permit & Planning Manager

Enc.: VA0021105 Permit and Fact Sheet

cc: DEQ-Water, OWPP

EPA-Region III, 3WP12

Department of Health, Culpeper

Water Compliance, NRO



COMMONWEALTH of VIRGINIA

DEPARTMENT OF ENVIRONMENTAL QUALITY

Permit No.

VA0021105

Effective Date: March 20, 2013

Expiration Date: March 19, 2018

AUTHORIZATION TO DISCHARGE UNDER THE VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM AND THE VIRGINIA STATE WATER CONTROL LAW

In compliance with the provisions of the Clean Water Act as amended and pursuant to the State Water Control Law and regulations adopted pursuant thereto, the following owner is authorized to discharge in accordance with the information submitted with the permit application, and with this permit cover page, Part I - Effluent Limitations and Monitoring Requirements, and Part II - Conditions Applicable To All VPDES Permits, as set forth herein.

Owner Name:

Rapidan Service Authority

Facility Name: Gordonsville Wastewater Treatment Plant

County: Orange

Facility Location: 735 Hill Road, Gordonsville, VA 22942

The owner is authorized to discharge to the following receiving stream:

Stream Name: South Anna River, UT

River Basin: York River

River Subbasin: None

Section:

3

Class: III

Special Standards: None

Thomas A. Faha

Director, Northern Regional Office Department of Environmental Quality

A. Effluent Limitations and Monitoring Requirements

1. Outfall 001 - 0.667 MGD Facility

- a. There shall be no discharge of floating solids or visible foam in other than trace amounts.
- b. During the period beginning with the permit's effective date and lasting until the expiration date or the issuance of the CTO for the 0.94 MGD facility, whichever occurs first, the permittee is authorized to discharge from Outfall Number 001. Such discharges shall be limited and monitored by the permittee as specified below.

Parameter	Discharge Limitations						Monitoring Requiremen		
	Monthly Avera	<u>ige⁽¹⁾</u>	Weekly	Average ⁽¹⁾	Minimum	Maximum ⁽¹⁾	Frequency	Sample Type	
Flow ⁽²⁾ (MGD)	NL		NA		NA	NL	Continuous	TIRE	
рН	NA	NA		NA		9.0 S.U.	1/D	Grab	
BOD ₅	10 mg/L 25	kg/day	15 mg/L	38 kg/day	NA	NA	3D/W	8H-C	
Total Suspended Solids, TSS	10 mg/L 25	kg/day	15 mg/L	38 kg/day	NA	NA	3D/W	8H-C	
Ammonia as N	2.3 mg/L		3.1 mg/L		NA	NA	3D/W	8H-C	
Dissolved Oxygen	NA		NA		6.5 mg/L	NA	1/D	Grab	
Total Residual Chlorine (after contact tank)	NA		NA		1.0 mg/L	NA	3/D at 4H intervals	Grab	
Total Residual Chlorine (after dechlorination)	0.008 mg/L		0.010 mg/L		NA	NA	3/D at 4H intervals	Grab	
E. coli (Geometric Mean)	126 n/100 mLs		NA		NA	NA	1/W	Grab	
(1) See Part I.B. (2) The design flow is 0.667 MGD.		 MGD = Million gallons per day. NA = Not applicable. NL = No limit; monitor and report. 				D = Once every of D = Three times of intervals.	lay. every day at 4 hours		
	S.U. = Standard units.					3D/\	3D/W = Three days per week.		
	TIRE = Totalizing, indicating and recording equipment.				ipment. 1/\	1/W = Once every week.			

⁸H-C = A flow proportional composite sample collected manually or automatically, and discretely or continuously, for the entire discharge of the monitored 8-hour period. Where discrete sampling is employed, the permittee shall collect a minimum of eight (8) aliquots for compositing. Discrete sampling may be flow proportioned either by varying the time interval between each aliquot or the volume of each aliquot. Time composite samples consisting of a minimum of eight (8) grab samples obtained at hourly or smaller intervals may be collected where the permittee demonstrates that the discharge flow rate (gallons per minute) does not vary by 10% or more during the monitored discharge.

Grab = An individual sample collected over a period of time not to exceed 15-minutes.

A. Effluent Limitations and Monitoring Requirements

2. Outfall 001 - 0.94 MGD Facility

- a. There shall be no discharge of floating solids or visible foam in other than trace amounts.
- b. In addition to any Total Nitrogen or Total Phosphorus concentration limits (or monitoring requirements without associated limits) listed below, this facility has Total Nitrogen and Total Phosphorus calendar year load limits associated with this outfall included in the current Registration List under registration number VAN030046, enforceable under the General VPDES Watershed Permit Regulation for Total Nitrogen and Total Phosphorus Dischargers and Nutrient Trading in the Chesapeake Watershed in Virginia.
- c. During the period beginning with the issuance of the CTO for the 0.94 MGD facility and lasting until the permit's expiration date, the permittee is authorized to discharge from Outfall Number 001. Such discharges shall be limited and monitored by the permittee as specified below.

Parameter		Discharge Limitations				Monitoring Requirements		
	Monthly	Average(1)	Weekly .	Average ⁽¹⁾	<u>Minimum</u>	Maximum ⁽¹⁾	Frequency	Sample Type
Flow ⁽²⁾ (MGD)	Ŋ	NL		NA		NL	Continuous	TIRE
рН	٨	ΙA	N	JA	6.0 S.U.	9.0 S.U.	1/D	Grab
cBOD ₅	10 mg/L	36 kg/day	15 mg/L	53 kg/day	NA	NA	3D/W	8H-C
Total Suspended Solids, TSS	10 mg/L	36 kg/day	15 mg/L	53 kg/day	NA	NA	3D/W	8H-C
Total Kjeldahl Nitrogen, TKN	3.0 mg/L	10 kg/day	4.5 mg/L	16 kg/day	NA	N/A	3D/W	8H-C
Dissolved Oxygen		NA		NA		NA	1/D	Grab
Total Residual Chlorine (after contact tank)	N	ΙA	٨	NΑ	1.0 mg/L	NA	3/D at 4H intervals	Grab
Total Residual Chlorine (after dechlorination)	0.008 mg/L		0.010) mg/L	NA	NA	3/D at 4H intervals	Grab
E. coli (Geometric Mean)	126 n/100 mLs		Ŋ	JA	NA	NA	1/W	Grab
NO2 + NO3 as Nitrogen	NL (mg/L)	N	JA	NA	NA	1/2W	8H-C
Total Nitrogen(3)	NL (mg/L)	N	JA	NA	NA	1/2W	Calculated
Total Nitrogen – Year to Date ⁽⁴⁾	NL (mg/L)	N	JA .	NA	NA	1/M	Calculated
Total Nitrogen - Calendar Year (4)	6.0	mg/L	١	١A	NA	NA	1/YR	Calculated
Total Phosphorus	NL (mg/L)	1	ĪΑ	NA	NA	1/2W	8H-C
Total Phosphorus - Year to Date(4)	NL (mg/L)	١	JΑ	NA	NA	1/M	Calculated
Total Phosphorus – Calendar Year (4)	0.4	mg/L	١	JA	NA	NA	1/YR	Calculated
(1) See Part I.B. (2) The design flow is 0.94 MGD. (3) Total Nitrogen and			MGD = Million gallons per day. NA = Not applicable. NI = No limit: monitor and report.		1/D = Once every day. 3/D = Three times every day. 3DAW = Three days every week			

(3) Total Nitrogen is the sum of Total Kjeldahl Nitrogen and NO₂+NO₃ Nitrogen and shall be calculated from the results of those tests.

(4) See Part I.B.4. for nutrient reporting calculations. The calendar year annual averages for Total Nitrogen and Total Phosphorus are effective January 1st of the year after issuance of the CTO for the expanded facility. NL = No limit; monitor and report.

S.U. = Standard Units.

TIRE = Totalizing, indicating and recording equipment.

3D/W = Three days every week.

1/W = Once every week.

I/M = Once every month.

1/2W = Once every two weeks at least 7 days apart.

1/YR = Once every year.

Grab = An individual sample collected over a period of time not to exceed 15-minutes.

⁸H-C = A flow proportional composite sample collected manually or automatically, and discretely or continuously, for the entire discharge of the monitored 8-hour period. Where discrete sampling is employed, the permittee shall collect a minimum of eight (8) aliquots for compositing. Discrete sampling may be flow proportioned either by varying the time interval between each aliquot or the volume of each aliquot. Time composite samples consisting of a minimum of eight (8) grab samples obtained at hourly or smaller intervals may be collected where the permittee demonstrates that the discharge flow rate (gallons per minute) does not vary by 10% or more during the monitored discharge.

A. Groundwater Monitoring Requirements

3. a. During the period beginning with the permit's effective date and lasting until the permit's expiration date, the permittee is required to monitoring the groundwater monitoring wells as specified in the Ground Water Monitoring Plan dated November 2002. The frequency of monitoring for the following groundwater monitoring wells; MW1, MW2, MW3, MW4, MW5, MW6, MW7, MW8, MW9, MW10, MW12, and MW13 shall be as follows:

PARAMETER	UNITS	LIMITATIONS	MONITORING REQUIREMENTS		
			Frequency	Sample Type	
Ground Water Elevation	Feet	NL	1/Y	Instantaneous	
рН	Standard Units	NL	1/Y	Grab	
Specific Conductance	Umhos/cm	NL	1/Y	Grab	
Nitrate Nitrogen	mg/L	NL	1/Y	Grab	
Total Organic Carbon (TOC)	mg/L	NL	1/Y	Grab	
Chlorides	mg/L	NL	1/Y	Grab	
Total Coliform	n/100 mL	NL	1/Y	Grab	
Total Sulfates	mg/L	NL	1/Y	Grab	
Total Kjeldahl Nitrogen	mg/L	NL	. 1/Y	Grab	
Ammonia Nitrogen	mg/L	NL	1/Y	Grab	
Total Recoverable Zinc	mg/L	NL ·	1/Y	Grab	

NL= No Limitation, Monitoring only required.

1/Y = Once per year.

- b. Samples taken in compliance with the monitoring requirements specified above shall be taken in accordance with the facility's groundwater monitoring plan.
- c. Pemittee is required to indicate the appropriate test method and the Quantification Level (QL) on each annual report.
- d. Minimum sample size for Conductivity is 500 mL, with maximum storage time of 28 days.
- e. The reporting year shall be the calendar year (January through December) and the groundwater data shall be submitted by the tenth of the month following the month in which the results were received.

B. Additional Monitoring Requirements, Quantification Levels and Compliance Reporting

- 1. Additional Total Residual Chlorine (TRC) Limitations and Monitoring Requirements
 - a. The permitee shall monitor the TRC at the outlet of the chlorine contact tank three times per day by grab sample.
 - b. No more than 9 taken at the outlet of the chlorine contact tank shall be less than 1.0 mg/L for any one calendar month.
 - c. No TRC sample collected at the outlet of the chlorine contact tank shall be less than 0.6 mg/L.
 - d. If dechlorination facilities exist the samples above shall be collected prior to dechlorination.
 - e. If chlorine disinfection is not used, E. coli shall be limited and monitored by the permittee as specified below:

	Discharge Limitations	<u>Monitoring</u>	
	Monthly Average	Frequency Requirements	Sample Type
E. coli	126 n/100ml	3Days/Week	Grab
	Geometric Mean		Between 10 AM & 4 PM

This E. coli requirement, if applicable, shall substitute for the TRC requirements delineated elsewhere in Part I.

2. Quantification Levels

a. The quantification levels (QL) shall be less than or equal to the following concentrations:

Characteristic	Quantification Level
TSS	1.0 mg/L
BOD ₅ /cBOD ₅	2 mg/L
Ammonia	0.20 mg/L
TRC	0.10 mg/L

- b. The QL is defined as the lowest concentration used to calibrate a measurement system in accordance with the procedures published for the method. The permittee shall use any method in accordance with Part II A of this permit.
- c. It is the responsibility of the permittee to ensure that proper quality assurance/quality control (QA/QC) protocols are followed during the sampling and analytical procedures. QA/QC information shall be documented to confirm that appropriate analytical procedures have been used and the required QLs have been attained.

3. Compliance Reporting for parameters in Part I.A.

- a. Monthly Average —Compliance with the monthly average limitations and/or reporting requirements for the parameters listed in Part I.B.2.a of this permit condition shall be determined as follows: All concentration data below the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.2.a above) shall be treated as zero. All concentration data equal to or above the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.2.a above) shall be treated as it is reported. An arithmetic average shall be calculated using all reported data for the month, including the defined zeros. This arithmetic average shall be reported on the Discharge Monitoring Report (DMR) as calculated. If all data are below the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.2.a above), then the average shall be reported as "<QL". If reporting for quantity is required on the DMR and the reported monthly average concentration is <QL, then report "<QL" for the quantity. Otherwise use the reported concentration data (including the defined zeros) and flow data for each sample day to determine the daily quantity and report the monthly average of the calculated daily quantities.
- b. Maximum Weekly Average –Compliance with the weekly average limitations and/or reporting requirements for the parameters listed in Part I.B.2.a of this permit condition shall be determined as follows: All concentration data below the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.2.a above) shall be treated as zero. All concentration data equal to or above the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.2.a above) shall be treated as reported. An arithmetic average shall be calculated using all reported data, including the defined zeros, collected within each complete calendar week and entirely contained within the reporting month. The maximum value of the weekly averages thus determined shall be reported on the DMR. If all data are below the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.2.a above), then the weekly average shall be reported as "<QL". If reporting for quantity is required on the DMR and the reported weekly average concentration is <QL, then report "<QL" for the quantity. Otherwise use the reported concentration data (including the defined zeros) and flow data for each sample day to determine the daily quantity and report the maximum weekly average of the calculated daily quantities.
- c. Single Datum Any single datum required shall be reported as "<QL" if it is less than the QL used in the analysis (QL must be less than or equal to the QL listed in Part I.B.2.a above). Otherwise the numerical value shall be reported.

- d. Significant Digits The permittee shall report at least the same number of significant digits as the permit limit for a given parameter. Regardless of the rounding convention used (i.e., 5 always rounding up or to the nearest even number) by the permittee, the permittee shall use the convention consistently, and shall ensure that consulting laboratories employed by the permittee use the same convention.
- 4. Nutrient Reporting Calculations for Part I. A.
 - a. For each calendar month, the DMR shall show the calendar year-to-date average concentration (mg/L) calculated in accordance with the following formulae:

$$MC_{avg}$$
-YTD = $(\sum_{(Jan-current month)} MC_{avg}) \div (\# of months)$

where

 MC_{avg} -YTD = calendar year-to-date average concentration (mg/L)

MC_{avg} = monthly average concentration (mg/L) as reported on DMR

b. The total nitrogen and phosphorus average concentrations (mg/L) for each calendar year (AC) shall be shown on the December DMR due January 10th of the following year. These values shall be calculated in accordance with the following formulae:

$$AC_{avg} = (\sum_{(Jan-Dec)} MC_{avg}) \div 12$$

where

 AC_{avg} = calendar year average concentration (mg/L)

 MC_{avg} = monthly average concentration (mg/L) as reported on DMR

- c. For Total Phosphorus, all daily concentration data below the quantification level (QL) for the analytical method used should be treated as half the QL. All daily concentration data equal to or above the QL for the analytical method used shall be treated as it is reported.
- d. For Total Nitrogen (TN), if none of the daily concentration data for the respective species (i.e., TKN, Nitrates/Nitrites) are equal to or above the QL for the respective analytical methods used, the daily TN concentration value reported shall equal one half of the largest QL used for the respective species. If one of the data is equal to or above the QL, the daily TN concentration value shall be treated as that data point is reported. If more than one of the data is above the QL, the daily TN concentration value shall equal the sum of the data points as reported.

C. Pretreatment Requirements

- 1. The permittee's pretreatment program is approved but is inactive. The program is an enforceable part of this permit. The permittee shall:
 - a. Within 180 days of the effective date of this permit, submit to DEQ-NRO a survey of all Industrial Users (IUs) discharging to the POTW. The information shall be submitted on the DEQ Discharger Survey Form or an equivalent form that includes information about the quantity and quality of the IU wastewater. Survey results shall include identify significant industrial users discharging to the POTW.
 - b. In lieu of the survey, the permittee may elect to develop, submit for approval and implement a plan to continuously survey the industrial community in their jurisdiction. This plan must be implemented within 90 days of its approval by DEQ.

- 2. Upon determination of receiving process wastewater from a Significant Industrial User (SIU)* to this treatment works, the permittee shall review all elements of the previously approved program and update each element as necessary. The elements are:
 - a. Legal authority,
 - b. Program procedures,
 - c. Funding and resources,
 - d. Local limits evaluation, and local limits if needed.
 - e. Enforcement response plan, and
 - f. List of SIUs.
- 3. All changes must be approved by DEQ prior to implementation. After all elements are approved, the pretreatment program will be considered active and the requirements below are in effect.
 - a. Implement the approved pretreatment program that complies with the Clean Water Act, Water Control Law and State regulations found at 9 VAC 25-31-730 through 900;
 - b. Submit to DEQ-NRO an annual report that describes the permittee's program activities over the previous year. The annual report shall be submitted no later than January 31 of each year and shall include:
 - 1) An updated list of the SIUs showing the categorical standards and local limits applicable to each. The updated list of the SIUs shall note all of the following:
 - a) Facility contact information (contact name, mailing address, e-mail address, telephone number(s));
 - b) Explanation of why SIUs were removed:
 - c) Identification of SIUs subject to Categorical Standards and the applicable standard(s) (i.e. metal finishing);
 - d) Applicable sections of 40 CFR;
 - e) SIUs subject to local limits that are more stringent than Categorical Pretreatment Standards;
 - f) SIUs subject only to local limits;
 - g) CIUs that are subject to reduced reporting requirements under 9 VAC 25-31-840 E.3.;
 - h) SIUs that are non-significant Categorical Industrial Users; and
 - i) The SIC and NAICs codes for all SIUs and CIUs.
 - 2) A summary of the compliance status of each SIU/IU with pretreatment standards and permit requirements.
 - 3) A summary of the number and types of SIU/IU sampling and inspections performed by the POTW.
 - 4) All information concerning interference, upset, VPDES permit, and/or Water Quality Standards violations directly attributable to SIUs*/IUs and associated enforcement actions taken.
 - 5) A description of all enforcement actions taken against SIUs*/IUs over the previous 12 months.
 - A summary of any changes to the submitted pretreatment program previously not reported to DEQ-NRO.
 - 7) A summary of the permits issued to SIUs*/IUs since the last annual report.
 - 8) POTW and self-monitoring results for SIUs* determined to be in significant non-compliance during the reporting period.

- 9) The results of POTW influent, effluent, and sludge sampling not previously submitted to DEQ-NRO.
- 10) Copies of newspaper publications of all SIUs* in significant non-compliance during the reporting period. This is due not later than March 31 of each year.
- 11) Signature of an authorized representative.
- c. Ensure all SIU permits are issued within 90 days of program approval and return to active status, subsequent SIU permits are reissued in a timely manner, and SIU permits issued or reissued by the POTW are effective and enforceable.
- d. Ensure all SIUs* shall be inspected at least annually.
 - Sampling shall include all regulated parameters and shall be representative of the wastewater discharged.
 - 2) Inspection of the SIUs* shall cover all areas that could result in wastewater discharge to the treatment works. At a minimum, this would include: manufacturing areas; chemical storage areas; pretreatment facilities; spill prevention and control procedures; hazardous waste generation; and the SIU's* selfmonitoring procedure and records.
- e. Implement the reporting requirements of Part VII of the VPDES Permit Regulation (9VAC 25-31-840).
- f. All public participation requirements shall be met. The SIUs* in significant non-compliance with pretreatment standards and/or requirements for the previous 12 month shall be placed in public notice annually.
- 4. DEQ may require the POTW to institute changes to the legal authority regarding SIU permits:
 - a. If the approved program does not meet the requirements of the Clean Water Act, the State Water Control Law or the state regulations;
 - b. If problems such as interferences, pass-through, violations of water quality standards or sludge contamination develop or continue; and
 - c. If federal, state or local requirements change.

5. A SIU is an industrial user that:

- a. Has a process wastewater flow (excluding sanitary, non-contact cooling water, boiler blowdown) of 25,000 gallons or more per average workday;
- Contributes a process wastestream which makes up 5% or more of the average dry weather hydraulic or organic capacity of the POTW;
- c. Is subject to the categorical pretreatment standards; or
- d. Has significant impact, either singularly or in combination with other SIUs on the treatment works or the quality of its effluent (e.g., causes pass through or interference).

D. Whole Effluent Toxicity Program Requirements

Biological Monitoring

a. The permittee shall initiate quarterly chronic toxicity tests ninety (90) days after the issuance of any Industrial User permit by the facility and shall continue quarterly toxicity testing for the remainder of the permit term. The permittee shall collect 8-hour flow-proportioned composite samples of final effluent from Outfall 001.

The chronic tests to use are:

Chronic 3-Brood Static Renewal Survival and Reproduction Test using Ceriodaphnia dubia

Chronic 7-Day Static Renewal Survival and Growth Test using Pimephales promelas

These chronic tests shall be conducted in such a manner and at sufficient dilutions (minimum of five dilutions) to determine the "No Observed Effect Concentration" (NOEC) for survival and reproduction or growth. Results which cannot be quantified (i.e., a "less than" NOEC value) are not acceptable and a retest shall be performed. The NOEC as determined by hypothesis testing shall be converted to TU_c (Chronic Toxic Units) for DMR reporting where $TU_c = 100/NOEC$. Report the LC_{50} at 48 hours and the IC_{25} with the NOEC in the test report.

- b. The permittee may provide additional samples to address data variability. These data shall be reported. Test procedures and reporting shall be in accordance with the WET testing methods cited in 40 CFR 136.3.
- c. The test dilutions shall be able to determine compliance with the following endpoints:

Chronic NOEC \geq 69%; equivalent to a TU_c \leq 1.44

- d. The test data will be evaluated statistically for reasonable potential at the conclusion of the test period. The data may be evaluated sooner if requested by the permittee or if toxicity has been noted. Should evaluation of the data indicate that a limit is warranted, a WET limit and compliance schedule will be required.
- e. The permit may be modified or revoked and reissued to include pollutant specific limits in lieu of a WET limit should it be demonstrated that toxicity is due to specific parameters. The pollutant specific limitation shall control the toxicity of the effluent.
- f. Should the results of any test exceed the endpoint cited above, the permittee shall conduct a retest of the effluent within 30 days.
- g. The permittee shall report the results and shall supply one copy of the toxicity test report to DEO-NRO.
- h. The quarterly monitoring periods shall be January through March, April through June, July through September and October through December. The DMR shall be submitted no later than the 10th day of the month following the monitoring period.

E. Groundwater Monitoring Program

1. The permittee submitted a groundwater monitoring plan dated November 2002. Beginning with this permit's effective date, the sampling parameters and frequency of analysis are as specified in Part I.A.3. The purpose of this plan is to determine if the system integrity is being maintained and to indicate if activities at the site are resulting in violations of the Board's Ground Water Standards. The groundwater monitoring plan is an enforceable part of the permit. Any changes to the plan must be submitted for approval to the DEQ-NRO.

- 2. Within 90 days of the permit's effective date, the permittee shall submit a groundwater monitoring well maintenance plan that details the following: 1) a maintenance schedule for cleaning the monitoring wells during this permit term; 2) a description of how the monitoring wells will be cleaned; and 3) a description of how the monitoring wells will be inspected to ensure that they are still in good working order.
- 3. The permittee shall submit an annual groundwater monitoring report that summarizes the evaluation of the groundwater monitoring well data for the preceding five years. This report shall analyze the groundwater data with respect to the appropriate Virginia Groundwater Standards, 9VAC25-280-40, 9VAC25-280-50, and 9VAC25-280-70. The reporting year shall be the calendar year (January through December) and shall be submitted by March 31st of the following year. If necessary, this annual report shall establish a corrective action plan to set forth the steps to be taken by the permittee to ensure that the contamination source is eliminated or that the contamination plume is contained on the permittee's property. In addition, based on the extent of contamination, a risk analysis may be required. Once approved, this plan and/or analysis shall be incorporated into the permit by reference and become an enforceable part of this permit.

F. Other Requirements and Special Conditions

1. 95% Capacity Reopener

A written notice and a plan of action for ensuring continued compliance with the terms of this permit shall be submitted to the DEQ-Northern Regional Office (DEQ-NRO) when the monthly average flow influent to the sewage treatment plant reaches 95 percent of the design capacity authorized in this permit for each month of any three consecutive month period. The written notice shall be submitted within 30 days and the plan of action shall be received at the DEQ-NRO no later than 90 days from the third consecutive month for which the flow reached 95 percent of the design capacity. The plan shall include the necessary steps and a prompt schedule of implementation for controlling any current or reasonably anticipated problem resulting from high influent flows. Failure to submit an adequate plan in a timely manner shall be deemed a violation of this permit.

2. <u>Indirect Dischargers</u>

The permittee shall provide adequate notice to the Department of the following:

- a. Any new introduction of pollutants into the treatment works from an indirect discharger which would be subject to Section 301 or 306 of Clean Water Act and the State Water Control Law if it were directly discharging those pollutants; and
- b. Any substantial change in the volume or character of pollutants being introduced into the treatment works by a source introducing pollutants into the treatment works at the time of issuance of this permit.
- c. Adequate notice shall include information on (i) the quality and quantity of effluent introduced into the treatment works, and (ii) any anticipated impact of the change on the quantity or quality of effluent to be discharged from the treatment works.

3. Operation and Maintenance (O&M) Manual Requirement

The permittee shall maintain a current Operations and Maintenance (O&M) Manual for the treatment works that is in accordance with Virginia Pollutant Discharge Elimination System Regulations, 9VAC25-31 and (for sewage treatment plants) Sewage Collection and Treatment Regulations, 9 VAC 25-790.

The O&M Manual and subsequent revisions shall include the manual effective date and meet Part II.K.2 and Part II.K.4 Signatory Requirements of the permit. Any changes in the practices and procedures followed by the permittee shall be documented in the O&M Manual within 90 days of the effective date of the changes. The permittee shall operate the treatment works in accordance with the O&M Manual and shall make the O&M manual available to Department personnel for review during facility inspections. Within 30 days of a request by DEQ, the current O&M Manual shall be submitted to the DEQ-NRO for review and approval.

The O&M manual shall detail the practices and procedures which will be followed to ensure compliance with the requirements of this permit. This manual shall include, but not necessarily be limited to, the following items, as appropriate:

- a. Permitted outfall locations and techniques to be employed in the collection, preservation, and analysis of effluent, storm water and sludge samples;
- b. Procedures for measuring and recording the duration and volume of treated wastewater discharged;
- c. Discussion of Best Management Practices, if applicable;
- d. Procedures for handling, storing, and disposing of all wastes, fluids, and pollutants that will prevent these materials from reaching state waters. List type and quantity of wastes, fluids, and pollutants (e.g. chemicals) stored at this facility;
- e. Discussion of treatment works design, treatment works operation, routine preventative maintenance of units within the treatment works, critical spare parts inventory and record keeping;
- f. Plan for the management and/or disposal of waste solids and residues;
- g. Hours of operation and staffing requirements for the plant to ensure effective operation of the treatment works and maintain permit compliance;
- h. List of facility, local and state emergency contacts; and
- i. Procedures for reporting and responding to any spills/overflows/ treatment works upsets.

4. Licensed Operator Requirement

The permittee shall employ or contract at least one Class II licensed wastewater works operator for this facility. The license shall be issued in accordance with Title 54.1 of the Code of Virginia and the regulations of the Board for Waterworks and Wastewater Works Operators. The permittee shall notify the Department in writing whenever he is not complying, or has grounds for anticipating he will not comply with this requirement. The notification shall include a statement of reasons and a prompt schedule for achieving compliance.

5. Reliability Class

The permitted treatment works shall meet Reliability Class II.

6. CTC and CTO Requirement

In accordance with Sewage Collection and Treatment regulation (9VAC25-790), the permittee shall obtain a Certificate to Construct (CTC) and a Certificate to Operate (CTO) from the Department of Environmental Quality prior to constructing wastewater treatment works and operating the treatment works, respectively. Non-compliance with the CTC or CTO shall be deemed a violation of the permit.

7. Sludge Reopener

The Board may promptly modify or revoke and reissue this permit if any applicable standard for sewage sludge use or disposal promulgated under Section 405(d) of the Clean Water Act is more stringent than any requirements for sludge use or disposal in this permit, or controls a pollutant or practice not limited in this permit.

8. Sludge Use and Disposal

The permittee shall conduct all sewage sludge use or disposal activities in accordance with the approved Sludge Management Plan (SMP). Any proposed changes in the sewage sludge use or disposal practices or procedures followed by the permittee shall be documented and submitted for DEQ-NRO approval 90 days prior to the effective date of the changes. Upon approval, the revised SMP becomes an enforceable part of the permit. The permit may be modified or alternatively revoked and reissued to incorporate limitations or conditions necessitated by substantive changes in sewage sludge use or disposal practices.

9. Total Maximum Daily Load (TMDL) Reopener

This permit shall be modified or alternatively revoked and reissued if any approved wasteload allocation procedure, pursuant to Section 303(d) of the Clean Water Act, imposes wasteload allocations, limits or conditions on the facility that are not consistent with the permit requirements.

10. Nutrient Offsets

Any annual Total Nitrogen and/or Total Phosphorus loadings above and beyond those permitted prior to July 1, 2005 shall be offset subject to a DEQ-approved trading contract prepared in accordance with 62.1-44.19:12 -: 19 of the Law and 9VAC25-820-10 et seq., and which includes, but not limited to, the following:

- a. Discussion of the source of the acquired allocations,
- b. Discussion of other permitted facilities involved in the trade, and
- c. Discussion of any non-point source allocations acquired.

This proposal shall provide for the waste loads that are projected to be discharged on an annual basis for the term of this permit, and shall be approved prior to the commencement of discharge from the new or expanded facility. Once approved, the conditions of the proposal pertaining to verification of non-point allocations acquired, or self-offsetting practices implemented, become an enforceable part of this permit.

11. E3/E4

The annual average concentration limitations for Total Nitrogen and/or Total Phosphorus are suspended during any calendar year in which the facility is considered by DEQ to be a participant in the Virginia Environmental Excellence Program in good standing at either the Exemplary Environmental Enterprise (E3) level or the Extraordinary Environmental Enterprise (E4) level, provided that the following conditions have also been met:

- a. The facility has applied for (or renewed) participation, been accepted, maintained a record of sustained compliance and submitted an annual report according to the program guidelines;
- b. The facility has demonstrated that they have in place a fully implemented environmental management system (EMS) with an alternative compliance method that includes operation of installed nutrient removal technologies to achieve the annual average concentration limitations; and
- c. The E3/E4 designation from DEQ and implementation of the EMS has been in effect for the full calendar year.

The annual average concentration limitations for Total Nitrogen and/or Total Phosphorus, as applicable, are not suspended in any calendar year following a year in which the facility failed to achieve the annual average concentration limitations as required by b. above.

12. Nutrient Reopener

This permit may be modified or, alternatively, revoked and reissued:

- a. If any approved wasteload allocation procedure, pursuant to Section 303(d) of the Clean Water Act, imposes wasteload allocations, limits or conditions on the facility that are not consistent with the permit requirements;
- b. To incorporate technology-based effluent concentration limitations for nutrients in conjunction with the installation of nutrient control technology, whether by new construction, expansion or upgrade, or
- c. To incorporate alternative nutrient limitations and/or monitoring requirements, should:
 - i. the State Water Control Board adopt new nutrient standards for the water body receiving the discharge, including the Chesapeake Bay or its tributaries, or
 - ii. a future water quality regulation or statute require new or alternative nutrient control.

13. Influent Flow Measurement

The influent flow shall be continuous recorded by totalizing, indicating and recording requirement. The daily flows shall be recorded and the influent monthly average shall be calculated on the monthly data sheet.

14. Overland Flow System

Wastewater application rates to the overflow system are to be recorded daily and reported monthly with the Discharge Monitoring Report (DMR).

Wastewater application to the overland flow system is prohibited during periods of significant rainfall events. Rainfall events are to measured and recorded daily and reported monthly with the DMR.

15. Calculation of Mass Data

These calculations shall be based upon effluent flow at the time of sampling. If at the time of sampling, the effluent flow exceeds the treatment works design flow due to rainfall events, then the mass data calculation shall be based on the wastewater volume applied to the overland flow fields for the previous 24-hour prior to the rainfall event.

CONDITIONS APPLICABLE TO ALL VPDES PERMITS

A. Monitoring

- 1. Samples and measurements taken as required by this permit shall be representative of the monitored activity.
- 2. Monitoring shall be conducted according to procedures approved under Title 40 Code of Federal Regulations Part 136 or alternative methods approved by the U.S. Environmental Protection Agency, unless other procedures have been specified in this permit.
- 3. The permittee shall periodically calibrate and perform maintenance procedures on all monitoring and analytical instrumentation at intervals that will insure accuracy of measurements.
- 4. Samples taken as required by this permit shall be analyzed in accordance with 1VAC30-45, Certification for Noncommercial Environmental Laboratories, or 1VAC30-46, Accreditation for Commercial Environmental Laboratories.

B. Records

- 1. Records of monitoring information shall include:
 - a. The date, exact place, and time of sampling or measurements;
 - b. The individual(s) who performed the sampling or measurements;
 - c. The date(s) and time(s) analyses were performed;
 - d. The individual(s) who performed the analyses;
 - e. The analytical techniques or methods used; and
 - f. The results of such analyses.
- 2. Except for records of monitoring information required by this permit related to the permittee's sewage sludge use and disposal activities, which shall be retained for a period of at least five years, the permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least 3 years from the date of the sample, measurement, report or application. This period of retention shall be extended automatically during the course of any unresolved litigation regarding the regulated activity or regarding control standards applicable to the permittee, or as requested by the Board.

C. Reporting Monitoring Results

1. The permittee shall submit the results of the monitoring required by this permit not later than the 10th day of the month after monitoring takes place, unless another reporting schedule is specified elsewhere in this permit. Monitoring results shall be submitted to:

Department of Environmental Quality - Northern Regional Office (DEQ-NRO) 13901 Crown Court Woodbridge, VA 22193

Monitoring results shall be reported on a Discharge Monitoring Report (DMR) or on forms provided, approved or specified by the Department.

2. If the permittee monitors any pollutant specifically addressed by this permit more frequently than required by this permit using test procedures approved under Title 40 of the Code of Federal Regulations Part 136 or using other test procedures approved by the U.S. Environmental Protection Agency or using

procedures specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR or reporting form specified by the Department.

3. Calculations for all limitations which require averaging of measurements shall utilize an arithmetic mean unless otherwise specified in this permit.

D. Duty to Provide Information

The permittee shall furnish to the Department, within a reasonable time, any information which the Board may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The Board may require the permittee to furnish, upon request, such plans, specifications, and other pertinent information as may be necessary to determine the effect of the wastes from this discharge on the quality of state waters, or such other information as may be necessary to accomplish the purposes of the State Water Control Law. The permittee shall also furnish to the Department upon request, copies of records required to be kept by this permit.

E. Compliance Schedule Reports

Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.

F. Unauthorized Discharges

Except in compliance with this permit, or another permit issued by the Board, it shall be unlawful for any person to:

- 1. Discharge into state waters sewage, industrial wastes, other wastes, or any noxious or deleterious substances; or
- 2. Otherwise alter the physical, chemical or biological properties of such state waters and make them detrimental to the public health, or to animal or aquatic life, or to the use of such waters for domestic or industrial consumption, or for recreation, or for other uses.

G. Reports of Unauthorized Discharges

Any permittee who discharges or causes or allows a discharge of sewage, industrial waste, other wastes or any noxious or deleterious substance into or upon state waters in violation of Part II.F.; or who discharges or causes or allows a discharge that may reasonably be expected to enter state waters in violation of Part II.F., shall notify the Department of the discharge immediately upon discovery of the discharge, but in no case later than 24 hours after said discovery. A written report of the unauthorized discharge shall be submitted to the Department, within five days of discovery of the discharge. The written report shall contain:

- 1. A description of the nature and location of the discharge;
- 2. The cause of the discharge;
- 3. The date on which the discharge occurred;
- 4. The length of time that the discharge continued;
- 5. The volume of the discharge;
- 6. If the discharge is continuing, how long it is expected to continue;
- 7. If the discharge is continuing, what the expected total volume of the discharge will be; and
- 8. Any steps planned or taken to reduce, eliminate and prevent a recurrence of the present discharge or any future discharges not authorized by this permit.

Discharges reportable to the Department under the immediate reporting requirements of other regulations are exempted from this requirement.

H. Reports of Unusual or Extraordinary Discharges

If any unusual or extraordinary discharge including a bypass or upset should occur from a treatment works and the discharge enters or could be expected to enter state waters, the permittee shall promptly notify, in no case later than 24 hours, the Department by telephone after the discovery of the discharge. This notification shall provide all available details of the incident, including any adverse affects on aquatic life and the known number of fish killed. The permittee shall reduce the report to writing and shall submit it to the Department within five days of discovery of the discharge in accordance with Part II.1.2. Unusual and extraordinary discharges include but are not limited to any discharge resulting from:

- 1. Unusual spillage of materials resulting directly or indirectly from processing operations;
- 2. Breakdown of processing or accessory equipment;
- 3. Failure or taking out of service some or all of the treatment works; and
- 4. Flooding or other acts of nature.

I. Reports of Noncompliance

The permittee shall report any noncompliance which may adversely affect state waters or may endanger public health.

- 1. An oral report shall be provided within 24 hours from the time the permittee becomes aware of the circumstances. The following shall be included as information which shall be reported within 24 hours under this paragraph:
 - a. Any unanticipated bypass; and
 - b. Any upset which causes a discharge to surface waters.
- 2. A written report shall be submitted within 5 days and shall contain:
 - a. A description of the noncompliance and its cause;
 - b. The period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and
 - c. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

The Board may waive the written report on a case-by-case basis for reports of noncompliance under Part II.I. if the oral report has been received within 24 hours and no adverse impact on state waters has been reported.

3. The permittee shall report all instances of noncompliance not reported under Parts II, I.1.or I.2., in writing, at the time the next monitoring reports are submitted. The reports shall contain the information listed in Part II.1.2.

NOTE: The immediate (within 24 hours) reports required in Parts II, G., H. and I. may be made to the Department's Northern Regional Office at (703) 583-3800 (voice) or (703) 583-3821 (fax). For reports outside normal working hours, leave a message and this shall fulfill the immediate reporting requirement. For emergencies, the Virginia Department of Emergency Services maintains a 24-hour telephone service at 1-800-468-8892.

J. Notice of Planned Changes

- 1. The permittee shall give notice to the Department as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required only when:
 - a. The permittee plans alteration or addition to any building, structure, facility, or installation from which there is or may be a discharge of pollutants, the construction of which commenced:
 - 1) After promulgation of standards of performance under Section 306 of Clean Water Act which are applicable to such source; or
 - 2) After proposal of standards of performance in accordance with Section 306 of Clean Water Act which are applicable to such source, but only if the standards are promulgated in accordance with Section 306 within 120 days of their proposal;
 - b. The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants which are subject neither to effluent limitations nor to notification requirements specified elsewhere in this permit; or
 - c. The alteration or addition results in a significant change in the permittee's sludge use or disposal practices, and such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing permit, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application plan.
- 2. The permittee shall give advance notice to the Department of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.

K. Signatory Requirements

- 1. All permit applications shall be signed as follows:
 - a. For a corporation: by a responsible corporate officer. For the purpose of this section, a responsible corporate officer means:
 - A president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy- or decision-making functions for the corporation, or
 - 2) The manager of one or more manufacturing, production, or operating facilities employing more than 250 persons or having gross annual sales or expenditures exceeding \$25 million (in secondquarter 1980 dollars), if authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures;
 - b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively; or
 - c. For a municipality, state, federal, or other public agency: by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a public agency includes:
 - 1) The chief executive officer of the agency, or
 - 2) A senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency.

- 2. All reports required by permits, and other information requested by the Board shall be signed by a person described in Part II.K.1., or by a duly authorized representative of that person. A person is a duly authorized representative only if:
 - a. The authorization is made in writing by a person described in Part II.K.1.;
 - b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company. (A duly authorized representative may thus be either a named individual or any individual occupying a named position.); and
 - c. The written authorization is submitted to the Department.
- 3. Changes to authorization. If an authorization under Part II.K.2. is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part II.K.2. shall be submitted to the Department prior to or together with any reports, or information to be signed by an authorized representative.
- 4. Certification. Any person signing a document under Parts II, K.1. or K.2. shall make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

L. Duty to Comply

The permittee shall comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the State Water Control Law and the Clean Water Act, except that noncompliance with certain provisions of this permit may constitute a violation of the State Water Control Law but not the Clean Water Act. Permit noncompliance is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or denial of a permit renewal application.

The permittee shall comply with effluent standards or prohibitions established under Section 307(a) of the Clean Water Act for toxic pollutants and with standards for sewage sludge use or disposal established under Section 405(d) of the Clean Water Act within the time provided in the regulations that establish these standards or prohibitions or standards for sewage sludge use or disposal, even if this permit has not yet been modified to incorporate the requirement.

M. Duty to Reapply

If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee shall apply for and obtain a new permit. All permittees with a currently effective permit shall submit a new application at least 180 days before the expiration date of the existing permit, unless permission for a later date has been granted by the Board. The Board shall not grant permission for applications to be submitted later than the expiration date of the existing permit.

N. Effect of a Permit

This permit does not convey any property rights in either real or personal property or any exclusive privileges, nor does it authorize any injury to private property or invasion of personal rights, or any infringement of federal, state or local law or regulations.

O. State Law

Nothing in this permit shall be construed to preclude the institution of any legal action under, or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any other state law or regulation or under authority preserved by Section 510 of the Clean Water Act. Except as provided in permit conditions on "bypassing" (Part II.U.), and "upset" (Part II.V.) nothing in this permit shall be construed to relieve the permittee from civil and criminal penalties for noncompliance.

P. Oil and Hazardous Substance Liability

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under Sections 62.1-44.34:14 through 62.1-44.34:23 of the State Water Control Law.

Q. Proper Operation and Maintenance

The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes effective plant performance, adequate funding, adequate staffing, and adequate laboratory and process controls, including appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by the permittee only when the operation is necessary to achieve compliance with the conditions of this permit.

R. Disposal of Solids or Sludges

Solids, sludges or other pollutants removed in the course of treatment or management of pollutants shall be disposed of in a manner so as to prevent any pollutant from such materials from entering state waters.

S. Duty to Mitigate

The permittee shall take all reasonable steps to minimize or prevent any discharge or sludge use or disposal in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

T. Need to Halt or Reduce Activity not a Defense

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

U. Bypass

1. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of Parts II, U.2. and U.3.

2. Notice

- a. Anticipated bypass. If the permittee knows in advance of the need for a bypass, prior notice shall be submitted, if possible at least ten days before the date of the bypass.
- b. Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required in Part II.I.

3. Prohibition of bypass.

- a. Bypass is prohibited, and the Board may take enforcement action against a permittee for bypass, unless:
 - 1) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
 - 2) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and
 - 3) The permittee submitted notices as required under Part II.U.2.
- b. The Board may approve an anticipated bypass, after considering its adverse effects, if the Board determines that it will meet the three conditions listed above in Part II.U.3.a.

V. Upset

- 1. An upset constitutes an affirmative defense to an action brought for noncompliance with technology based permit effluent limitations if the requirements of Part II.V.2. are met. A determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is not a final administrative action subject to judicial review.
- 2. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
 - a. An upset occurred and that the permittee can identify the cause(s) of the upset;
 - b. The permitted facility was at the time being properly operated;
 - c. The permittee submitted notice of the upset as required in Part II.I.; and
 - d. The permittee complied with any remedial measures required under Part II.S.
- 3. In any enforcement proceeding the permittee seeking to establish the occurrence of an upset has the burden of proof.

W. Inspection and Entry

The permittee shall allow the Director, or an authorized representative, upon presentation of credentials and other documents as may be required by law, to:

1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;

- 2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- 3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
- 4. Sample or monitor at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by the Clean Water Act and the State Water Control Law, any substances or parameters at any location.

For purposes of this section, the time for inspection shall be deemed reasonable during regular business hours, and whenever the facility is discharging. Nothing contained herein shall make an inspection unreasonable during an emergency.

X. Permit Actions

Permits may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.

Y. Transfer of Permits

- Permits are not transferable to any person except after notice to the Department. Except as provided in Part II.Y.2., a permit may be transferred by the permittee to a new owner or operator only if the permit has been modified or revoked and reissued, or a minor modification made, to identify the new permittee and incorporate such other requirements as may be necessary under the State Water Control Law and the Clean Water Act.
- 2. As an alternative to transfers under Part II.Y.1., this permit may be automatically transferred to a new permittee if:
 - a. The current permittee notifies the Department at least 30 days in advance of the proposed transfer of the title to the facility or property;
 - b. The notice includes a written agreement between the existing and new permittees containing a specific date for transfer of permit responsibility, coverage, and liability between them; and
 - c. The Board does not notify the existing permittee and the proposed new permittee of its intent to modify or revoke and reissue the permit. If this notice is not received, the transfer is effective on the date specified in the agreement mentioned in Part II.Y.2.b.

Z. Severability

The provisions of this permit are severable, and if any provision of this permit or the application of any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.